Productcode 73382



## **AUTOGEAR POWER MTF 75W-90**

**Manual transmission fluid** 

**AUTOGEAR POWER MTF 75W-90** is a high quality manual transmission fluid designed for passenger- and light commercial vehicles using both manual transmissions and transaxles. Not suitable for differentials and other API GL-5 applications.

**AUTOGEAR POWER MTF 75W-90** is based on high quality synthetic technology base oil in combination with a special additive package to ensure the following properties:

- Exceptional thermo-oxidative stability.
- Superior lubricating properties provide improved fuel economy.
- Exceptional load bearing characteristics.
- Effective rust and corrosion protection.
- Outstanding low temperature fluidity provides smoother shifting at low ambient temperatures.
- Good gear engagement with a variety of synchronizer materials including brass, carbon, sintered bronze and molybdenum

AUTOGEAR POWER MTF 75W-90 meets the following performance criteria:

API GL-4	BMW MTF LT-4	Ford WSD-M2C200-C	Ford WSS-M2C200-D2
GM 1940182	GM 1940764	GM 1940004	VW G50 (VW 501 50)

## **Typical Analysis**

Properties	Unit	Method	Typical Value
SAE Grade		SAE J306	75W-90
Density @15°C	kg/m³	ASTM 4052	877
Kinematic Viscosity @ 40°C	mm²/s	ASTM D7042	109
Kinematic Viscosity @ 100°C	mm²/s	ASTM D7042	17.8
Viscosity Index		ASTM D2270	183
Brookfield Viscosity @-40°C	сР	ASTM D2983	<150 000
Flash Point COC	°C	ASTM D92	>201
Pour Point	°C	ASTM D7346	-39
Date Issued: 08-06-2020	Supersedes: -	Revision Nr.: -	